



 POLARIS
SPORTSMAN


SPORTSMAN 570 EFI

SPORTSMAN 570 EPS

SPORTSMAN X2 570 EPS

SPORTSMAN 850

SPORTSMAN 850 SP

SPORTSMAN XP 1000

SCRAMBLER XP® 1000

| | | | | | | | |
|--|--|--|--|--|--|--|---|
| Engine Type | 4-Stroke DOHC Single Cylinder | 4-Stroke DOHC Single Cylinder | 4-Stroke DOHC Single Cylinder | 4-Stroke SOHC Twin Cylinder | 4-Stroke SOHC Twin Cylinder | 4-Stroke SOHC Twin Cylinder | 4-Stroke SOHC Twin Cylinder |
| Displacement/HP | 567 cc | 567 cc | 567 cc | 850 cc | 850 cc | 952 cc | 952 cc |
| Fuel System | Electronic Fuel Injection | Electronic Fuel Injection | Electronic Fuel Injection | Electronic Fuel Injection | Electronic Fuel Injection | Electronic Fuel Injection | Electronic Fuel Injection |
| Cooling | Liquid | Liquid | Liquid | Liquid | Liquid | Liquid | Liquid |
| Transmission/Final Drive | Automatic PVT H/L/N/R/P | Automatic PVT H/L/N/R/P | Automatic PVT H/L/N/R/P | Automatic PVT H/L/N/R/P | Automatic PVT H/L/N/R/P | Automatic PVT H/L/N/R/P | Automatic PVT H/L/N/R/P |
| Drive System | On-Demand True AWD/2WD | On-Demand True AWD/2WD | Close Ratio On-Demand True AWD/2WD w/Versa Trac Turf Mode | On-Demand True AWD/2WD | High Performance On-Demand True AWD/2WD | High Performance On-Demand True AWD/2WD | High Performance On-Demand True AWD/2WD |
| Engine Braking System/Active Descent Control | Not Equipped | Standard | Standard | Standard | Standard | Standard | Not Equipped |
| Front Suspension | MacPherson Strut 208 mm Travel | MacPherson Strut 208 mm Travel | MacPherson Strut 208 mm Travel | Dual A-Arm 229 mm Travel | Dual A-Arm 229 mm Travel | High Clearance Arched Dual A-Arm 229 mm Travel | Dual A-Arm 229 mm Travel |
| Rear Suspension | Dual A-Arm, IRS 241 mm Travel | Dual A-Arm, IRS 241 mm Travel | Dual A-Arm, IRS 241 mm Travel | Dual A-Arm, IRS 260 mm Travel | Dual A-Arm, IRS 260 mm Travel | High Clearance Arched Dual A-Arm, Rolled IRS 260 mm Travel | Dual A-Arm, Rolled IRS 260 mm Travel |
| Front/Rear Brakes | Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake | Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake | Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake | Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake | Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake | Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake | Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake |
| Front Tyres | 25 x 8-12; 489 | 25 x 8-12; 489 | 25 x 8-12; 489 | 25 x 8-14; CST | 25 x 8-14; CST | 26 x 8-14; PXT 6 Ply Radial | 26 x 8-14; CST |
| Rear Tyres | 25 x 10-12; 489 | 25 x 10-12; 489 | 25 x 10-12; 489 | 25 x 10-14; CST | 25 x 10-14; CST | 26 x 10-14; PXT 6 Ply Radial | 26 x 10-14; CST |
| Wheels | Stamped Steel | Stamped Steel | Stamped Steel | Stamped Steel | Cast Aluminium | Cast Aluminium | Cast Aluminium |
| Wheelbase | 1283 mm | 1283 mm | 1422 mm | 1346 mm | 1346 mm | 1346 mm | 1346 mm |
| Dry Weight | 330 Kg | 330 Kg | 358 Kg | 342 Kg | 349 Kg | 392 Kg | 338 Kg |
| Overall Vehicle Size (LxWxH) | 2108 x 1219 x 1219 mm | 2108 x 1219 x 1219 mm | 2184 x 1219 x 1219 mm | 2114 x 1209 x 1289 mm | 2114 x 1209 x 1289 mm | 2114 x 1209 x 1289 mm | 2090 x 1230 x 1230 mm |
| Ground Clearance | 279 mm | 279 mm | 279 mm | 292 mm | 292 mm | 292 mm | 292 mm |
| Fuel Capacity | 17 L | 17 L | 17 L | 20 L | 20 L | 20 L | 20 L |
| Bed Box Dimensions (LxWxH) | N.A. | N.A. | 950 x 495 x 165 mm | N.A. | N.A. | N.A. | N.A. |
| Front/Rear Rack or Box Capacity | 41 Kg / 82 Kg | 41 Kg / 82 Kg | 41 Kg / 180 Kg | 55 Kg / 110 Kg | 55 Kg / 110 Kg | 55 Kg / 110 Kg | 11 Kg / 23 Kg |
| Payload Capacity | 220 Kg | 220 Kg | 320 Kg | 261 Kg | 261 Kg | 261 Kg | 131 Kg |
| Hitch Tow Rating | 556 Kg | 556 Kg | 556 Kg | 680 Kg | 680 Kg | 680 Kg | 680 Kg |
| Hitch/Type | Standard / 1.25" Receiver | Standard / 1.25" Receiver | Standard / 1.25" Receiver | Standard / 1.25" Receiver | Standard / 1.25" Receiver | Standard / 1.25" Receiver | Standard / 1.25" Receiver |
| Lighting | 50W High Beam, Dual 50W Low Beam Headlights; Dual Taillights Breaklights | 50W High Beam, Dual 50W Low Beam Headlights; Dual Taillights Breaklights | Triple 50W High Beam, Dual 50W Low Beam Headlights; Dual Taillights Breaklights | Triple 50W High Beam, Dual 50W Low Beam Headlights; Dual Taillights Breaklights | Triple 50W High Beam, Dual 50W Low Beam Headlights; Dual Taillights Breaklights | Triple 50W High Beam, Dual 50W Low Beam Headlights; Dual Taillights Breaklights | White LED; Hi/Low Beam; Single Rear Taillight |
| Electronic Power Steering | N.A. | Standard | Standard | N.A. | Standard | Standard | Standard |
| Colours |  Sage Green |  Sage Green |  Sage Green |  Sage Green |  Pursuit Camo |  Pursuit Camo |  Titanium Matte Metallic |

For more information and specifications visit
www.polarissa.co.za

Polaris South Africa supports responsible riding. For your safety, always wear a helmet, eye protection, protective clothing and never carry passengers unless the ATV or Side x Side has been designed by the manufacturer specifically for that purpose. Models are for riders aged 16 years and older. Contact your dealer for colour options.